
J. WEGNER, S. CEYLAN, C. FRIESE, A. KIRSCHNING* (LEIBNIZ UNIVERSITÄT HANNOVER AND PIT – PLASMA INDUCTION TECHNOLOGY, DÜSSELDORF, GERMANY)

Inductively Heated Oxides Inside Microreactors – Facile Oxidations under Flow Conditions *Eur. J. Org. Chem.* **2010**, 4372-4375.

Facile Oxidations under Flow Conditions in Fixed-Bed Reactors



Significance: Flow oxidation with inductive heating inside flow reactors was described. The oxidation reactions of various substrates were carried out in glass flow reactors charged with superparamagnetic nanoparticles and solid oxidants, which were exposed to a magnetic field with an inductive frequency of 25 kHz at 40 psi backpressure to afford the corresponding products.

Comment: The flow oxidation of substrates **9**, **11** or **19** was performed by using a PEEK (polyether ether ketone) reactor at 100 psi backpressure. The authors previously reported the first application of ferromagnetic materials like magnetic nanoparticles Fe_3O_4 coated with a silica shell (10–40 nm) as heating media in flow reactions (*Angew. Chem. Int. Ed.* **2008**, *47*, 8950).

SYNFACTS Contributors: Yasuhiro Uozumi, Yoichi M. A. Yamada, Maki Minakawa Synfacts 2010, 11, 1313-1313 Published online: 21.10.2010 **DOI:** 10.1055/s-0030-1258824; **Reg-No.:** Y11010SF

Polymer-Supported Synthesis

Key words

Category

inductive heating oxidation flow conditions metal oxides

